

## MOMENTARY HOLD-UP BUTTON

**0E-HBMOMSD3T**  
**SINGLE POLE, DOUBLE THROW**  
**3 SCREW TERMINALS**



Applications include silent alarm, door and access control, video surveillance recording, machinery and others, including simultaneous activation or deactivation of multiple devices. Activation is nearly silent. Momentary button. Durable ABS plastic housing.

- MOMENTARY OPERATION
- RECESSED BUTTON PREVENTS ACCIDENTAL ACTIVATION
- SINGLE POLE, DOUBLE THROW CONTACTS
- LONG-LIFE SWITCH WITH 10A CURRENT RATING
- 125 TO 250VAC VOLTAGE RATING
- 3 SCREW TERMINALS
- OPERATING TEMP.: -35°F to 180°F (-37°C to 82°C)
- STORAGE TEMP.: -35°F to 180°F (-37°C to 82°C)
- HUMIDITY: 0 TO 95%

PART #: 0E-HBMOMSD3T

UPC: 811914023456

LENGTH: 2.4"

WIDTH: 2.2"

HEIGHT: 1"

WEIGHT: 1.8 OUNCES

SECURITY  
SIGNALING  
 LISTED  
E478233

CE RoHS



**W BOX**  
TECHNOLOGIES

**FOR MORE INFORMATION,  
CONTACT YOUR ADI SALES PERSON.**

[wboxtech.com](http://wboxtech.com)