

SPEC SHEET



1 AMP 120VAC/2 AMP 28VDC RELAY MODULE

0E-RLY6242A

1A 120VAC OR 2A 28VDC DPDT CONTACTS
6, 12 OR 24VDC OPERATION



Applications include intrusion, access control, video surveillance and other systems requiring control or activation of electronic devices. Operations include dry contacts, latching dry contacts, polarity reversal and line seizure. Includes double-sided foam mounting tape.

- 6, 12 OR 24VDC SELECTABLE OPERATION
- 1 AMP 120VAC OR 2A 28VDC DPDT CONTACTS
- 30 MA CURRENT DRAW
- AC INPUT REQUIRED: 6VDC 1.8VA, 12VDC 3.6VA, 24VDC 7.2A
- OPERATING TEMP.: -13°F to 131°F (-25°C to 55°C)
- STORAGE TEMP.: -13°F to 158°F (-25°C to 70°C)
- HUMIDITY: 0 TO 95%

PART #: 0E-RLY6242A

UPC: 811914023432

LENGTH: 2.75"

WIDTH: 2"

HEIGHT: 1"

WEIGHT: 1.6 OUNCES

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.



wboxtech.com