

HD TVI TURRET CAMERA

1080P IR Outdoor Turret Camera



The 0E-HDD2812W is a 2.1 MP (1920 X 1080) turret camera constructed with a 2.8mm-12mm motorized lens. This 2.1 MP Camera is IP66 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- 2.8-12 mm lens
- IR up to 40M (131 ft)
- 1920 X 1080 Picture Quality
- DNR & WDR
- TVI + CVBS Dual Output
- OSD Menu
- True Day Night
- Operating Temperature -40 °C – 60 °C (-40 °F – 140 °F)
- Max. 6W Power Consumption
- IP 66 Rated
- 12V DC
- 3 Year Warranty

PART #: 0E-HDD2812W

UPC: 811914024286

LENGTH: 5.29"

WIDTH: 4.88"

HEIGHT: 4.39"

WEIGHT: 26.5 ounces

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.

FOR TECHNICAL SUPPORT: 1-888-668-8808



Specifications

Model	0E-HDB36W	0E-HDB2812W	0E-HDD2812W
Camera			
Image Sensor	2MP CMOS Image Sensor		
Effective Pixels	1928(H)*1088(V)		
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR		
Shutter Speed	1/30 s to 1/50,000 s		
Lens	3.6mm	2.8-12mm	
	Angle of view: 82.2°	Angle of view: 35.1°-114.5°	
Angle Adjustment	Pan:0°-360°;Tilt:0°-90°;Rotate:0°-360°		Pan:0°-360°;Tilt:0°-75°;Rotate:0°-360°
Day &Night	ICR		
Digital Noise Reduction	Yes		
HD Video Output	1 Analog HD output		
Video Frame Rate	1920 × 1080@30fps		
Menu	White Balance, BLC, AGC, D/N Mode Function:Wide Dynamic Range; Digital Noise reduction; Mirror; SMART IR		
General			
Operating Conditions	-40° C – 60° C (-40° F – 140° F); Humidity 90% or less (non-condensing)		
Power Supply	12 VDC ± 15%		
Power Consumption	Max. 5 W	Max. 6 W	
Ingress Protection level	IP66		
IR Range	Up to 20m	Up to 40m	
Dimensions	58.5mm×55.5mm×153.6mm (2.30"×2.19"×6.05")	92mm×89mm×269.6mm (3.6"×3.5"×10.6")	134.3mm×123.9mm×111.4mm (5.29"×4.88"×4.39")
Weight	370g (0.82lb)	900g (1.98lb)	750g (1.57lb)