

IP BULLET CAMERA

2.1 MP IR Outdoor Bullet Camera



The 0E-21BF40WDR is a 2.1 MP (1920 X 1080) bullet camera constructed with a 4mm lens. This 2.1 MP Camera is IP67 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- 4 mm lens
- 30 IR LEDs
- IR Distance: 30 m/100 ft
- 3-axis Gimbal
- 3D Digital Noise Reduction
- True Wide Dynamic Range
- Onvif Supported
- IP 67 Rated
- PoE/12 VDC
- 5 Year Warranty

PART #: 0E-21BF40WDR

UPC: 811914026006

LENGTH: 2.8"

WIDTH: 6.2"

HEIGHT: 2.4"

WEIGHT: 17.64 ounces

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.

ONVIF



FOR TECHNICAL SUPPORT: 1-888-668-8808

Specifications

Model	OE-21BF40WDR	OE-40BF40WDR	OE-21DF28WDR	OE-40DF28WDR
Camera				
Image Sensor	1/2.8" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR			
Shutter Speed	1/3 s to 1/10,000 s			
Lens	4mm@ F2.0		2.8mm@ F2.0	
	Angle of view: 90°	Angle of view: 83°	Angle of view: 115°	Angle of view: 106°
Day &Night	IR cut filter with auto switch			
Digital Noise Reduction	3D DNR			
Wide Dynamic Range	120dB			
P&T rotation	/		Pan: 0° ~ 355°, Tilt: 0° ~ 75°, Rotation: 0° ~ 355°	
Compression Standard				
Video Compression	H.264 / MJPEG/H.264+			
Video Bit Rate	32 Kbps – 16 Mbps			
Image				
Max. Resolution	1920 x 1080	2688×1520	1920 × 1080	2688×1520
Frame Rate	30fps (1920×1080), 30fps(1280×960), 30fps(1280×720)	20fps(2688×1520), 30fps(1920×1080), 30fps(1280×720)	30fps (1920×1080), 30fps(1280×960), 30fps(1280×720)	20fps(2688×1520), 30fps(1920×1080), 30fps(1280×720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser			
Backlight compensation	Yes, zone optional			
Network				
Network Storage	NAS (Support NFS,SMB/CIFS), ANR			
Detection	Motion detection, Dynamic analysis			
Alarm Trigger	Tampering alarm, Network disconnect , IP address conflict, Storage exception			
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour			
General	Anti-flicker, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access			
Standard	ONVIF, PSIA, CGI, ISAPI			
Interface				
Communication Interface	1 RJ-45 10M/100M Ethernet interface			
General				
Operating Conditions	-30° C – 60° C (-22° F – 140° F); Humidity 95% or less (non-condensing)			
Power Supply	12 VDC ± 25%; PoE (802.3af)			
Power Consumption	Max. 5 W			
Ingress Protection level	IP67			
Impact Protection	/		K10	
IR Range	30 meters			
Dimensions	70×154.2×60.5 mm (2.8" × 6.2" × 2.4")		Φ111 × 82 (4.4" × 3.2")	
Weight	500 g (1.1 lbs)			