

IP DOME CAMERA

4 MP IP Vandal Dome Camera



The 0E-40DF28WDR is a 4 MP (2688×1520) dome camera constructed with a 2.8mm lens. This 4 MP Camera is IP67/IK10 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- 2.8 mm lens
- 30 IR LEDs
- IR Distance: 30 m/100 ft
- 3-axis Gimbal
- 3D Digital Noise Reduction
- True Wide Dynamic Range
- Onvif Supported
- IP 67/IK10 Rated
- PoE/12 VDC
- 5 Year Warranty

PART #: 0E-40DF28WDR

UPC: 811914026037

LENGTH: 4.4"

WIDTH: 4.4"

HEIGHT: 3.2"

WEIGHT: 17.64 ounces

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.

Onvif



FOR TECHNICAL SUPPORT: 1-888-668-8808

Specifications

Model	OE-21BF40WDR	OE-40BF40WDR	OE-21DF28WDR	OE-40DF28WDR
Camera				
Image Sensor	1/2.8" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR			
Shutter Speed	1/3 s to 1/10,000 s			
Lens	4mm@ F2.0		2.8mm@ F2.0	
	Angle of view: 90°	Angle of view: 83°	Angle of view: 115°	Angle of view: 106°
Day &Night	IR cut filter with auto switch			
Digital Noise Reduction	3D DNR			
Wide Dynamic Range	120dB			
P&T rotation	/		Pan: 0° ~ 355°, Tilt: 0° ~ 75°, Rotation: 0° ~ 355°	
Compression Standard				
Video Compression	H.264 / MJPEG/H.264+			
Video Bit Rate	32 Kbps – 16 Mbps			
Image				
Max. Resolution	1920 x 1080	2688x1520	1920 x 1080	2688x1520
Frame Rate	30fps (1920x1080), 30fps(1280x960), 30fps(1280x720)	20fps(2688x1520), 30fps(1920x1080), 30fps(1280x720)	30fps (1920x1080), 30fps(1280x960), 30fps(1280x720)	20fps(2688x1520), 30fps(1920x1080), 30fps(1280x720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser			
Backlight compensation	Yes, zone optional			
Network				
Network Storage	NAS (Support NFS,SMB/CIFS), ANR			
Detection	Motion detection, Dynamic analysis			
Alarm Trigger	Tampering alarm, Network disconnect , IP address conflict, Storage exception			
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour			
General	Anti-flicker, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access			
Standard	ONVIF, PSIA, CGI, ISAPI			
Interface				
Communication Interface	1 RJ-45 10M/100M Ethernet interface			
General				
Operating Conditions	-30° C – 60° C (-22° F – 140° F); Humidity 95% or less (non-condensing)			
Power Supply	12 VDC ± 25%; PoE (802.3af)			
Power Consumption	Max. 5 W			
Ingress Protection level	IP67			
Impact Protection	/		K10	
IR Range	30 meters			
Dimensions	70x154.2x60.5 mm (2.8" x 6.2" x 2.4")		Φ111 x 82 (4.4" x 3.2")	
Weight	500 g (1.1 lbs)			