

## NETWORK VIDEO RECORDER

4 Channel 4 PoE Ports  
2TB Hard Drive Included



The OE-4CHNVR2TB is a 4 channel Network Video Recorder constructed with 4 PoE ports and 2TB hard drive storage. This new generation NVR is widely applied in the areas of public security, education, communication, transportation, military, finance/banking and various other installation applications.

- Linux Embedded System
- H.264/MPEG-4 Video Stream Input
- HDMI/VGA Output 1920 x 1080
- PoE Supported
- 2TB Hard Drive Included
- Maximum Storage Capacity: 6 TB
- Remote Live View By Mobile App
- 5 Year Limited Warranty (Excluding Hard Drive)
- 3 Year Limited Warranty (Hard Drive in Recorder)

PART #: OE-4CHNVR2TB

UPC: 811914028932

LENGTH: 10.1"

WIDTH: 9.25"

HEIGHT: 1.8"

WEIGHT: 2.1bs



**FOR MORE INFORMATION,  
CONTACT YOUR ADI SALES PERSON.  
FOR TECHNICAL SUPPORT: 1-888-888-8997**

[wboxtech.com](http://wboxtech.com)

# Specifications

<b>Model</b>	0E-4CHNVR2TB
<b>VIDEO/AUDIO INPUT</b>	
<b>Video Input</b>	4ch
<b>Incoming Bandwidth</b>	40Mbps ,(main stream 32Mbps ,sub stream 8Mbps)
<b>Outgoing Bandwidth</b>	Total 80Mbps
<b>Audio Input</b>	G711_A/G711_U
<b>VIDEO/AUDIO OUTPUT</b>	
<b>Live View/Playback/ Recording Resolution</b>	6MP/5MP/4MP/3MP/1080P/960P/720P/D1/VGA/CIF/QCIF
<b>Frame Rate</b>	6MP/5MP/4MP/3MP@15fps; 1080P@30fps;
<b>Live View/Playback Resolution</b>	Live View: 4ch 1080P/1ch 6MP,@30fps Playback: 4ch 1080P/1ch 6MP
<b>HDMI/VGA Output</b>	1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz
<b>Audio Output</b>	1ch, line out
<b>HARD DISK</b>	
<b>SATA HDD</b>	1 SATA interface for 1HDD
<b>Mounting Mode</b>	Embedded
<b>Capacity</b>	Up to 6TB for each disk
<b>NETWORK</b>	
<b>Network Interface</b>	1 RJ45 10M/100M network interface
<b>Protocol</b>	RTP/RTCP,TCP/UDP,HTTP,DHCP,DNS,NTP
<b>POE Interface</b>	4ch 100Mbps ,IEEE802.3af
<b>POE Max Power</b>	36W
<b>INTERFACE</b>	
<b>HDMI/VGA</b>	1ch HDMI, 1ch VGA
<b>USB</b>	USB 2.0 x2
<b>Audio I/O</b>	1 in, 1 out
<b>Alarm I/O</b>	2in, 2 out
<b>Reset Button</b>	Yes
<b>GENERAL</b>	
<b>Power Supply</b>	DC 48V –DC52V,Max Input 70W
<b>Power Consumption</b>	Max 10W(without HDD,USB,POE)
<b>Operating Temperature</b>	-10°C ~ 45°C (14°F ~ 113°F )
<b>Operating Humidity</b>	0% - 90% RH
<b>Chassis</b>	Smart 1U
<b>Product Dimensions</b>	255x235x47.5mm
<b>Product Weight</b>	930g