

IP EYEBALL CAMERA

4 MP IP Eyeball Camera



The 0E-4MPMOEYE is a 4 MP(2592×1520)Eyeball camera constructed with a motorized lens. This 4 MP Camera is IP67 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- Motorized 2.7 ~13.5mm lens
- 15 IR LEDs
- IR Distance: 40 m/131 ft
- 3-axis Gimbal
- 3D Digital Noise Reduction
- True Wide Dynamic Range
- Onvif Supported
- IP 67 Rated
- PoE/12 VDC
- 5 Year Warranty

PART #: 0E-4MPMOEYE

UPC: 840049300965

LENGTH: 5.7"

HEIGHT: 4.6"

WEIGHT: 0.77 Lbs.

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.

Onvif



FOR TECHNICAL SUPPORT: 1-833-574-9124

Specifications

Model	0E-4MPMOEYE
Image Sensor	1/3" Progressive Scan CMOS
Min. illumination	Color :0.05Lux@(F1.2,AGC ON);B/W: 0 Lux@(IR LED ON)
Day & Night	ICR
Shutter Speed	1/5-1/20000
Auto Iris	Motorized
Wide Dynamic Range	WDR >120dB
Digital Noise Reduction	2D/3D
Lens	2.7~13.5 mm
FOV	103~34.3°
IR LED	24pcs
IR Range	40m
IMAGE	
Video Compression	H.265/H.264/ MJPEG
Bit Rate (CBR/VBR)	Main stream: 500Kbps~12Mbps ; Sub stream 100Kbps~6Mbps
Audio Compression	N/A
Max. Resolution	2592x1520/30fps
Stream	Stream 1 2592x1520/2560x1440/2304x1296/1920x1080/1280x720 Stream 2 D1 to QVGA Stream 3 VGA/CIF/QVGA
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC	Yes
9:16 Corridor mode	Yes
ROI	Yes
Defog	Yes
NETWORK	
Network Protocols:	IPv4,802.1x,HTTP,HTTPS,TCP/IP,UDP/IP,RTSP,DHCP,NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP ,IGMP, Unicast and Multicast
Alarm Trigger	Motion Detection, Network Disconnect, Disk Alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish. Russian, French, Czech, Hungarian
System Compatibility	Onvif Supported
Interface	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
GENERAL	
Power Supply	DC12V/POE
Power Consumption	2.5W(IR LED OFF); 6.5 W (IR LED ON)
Operating Temperature	Starting Temperature: -30°C ~ 50°C (22°F ~ 122°F) Working Temperature: -30°C ~ 50°C (-22°F ~ 122°F)
Operating Humidity	0% - 90% RH
Ingress Protection	IP67
Product Dimensions	Φ119*110mm
Product Weight	650g