

NETWORK VIDEO RECORDER

4 Channel 4 PoE Ports
1TB Hard Drive Included



The OE-4CHNVRNG is a 4 channel Network Video Recorder constructed with 4 PoE ports and 1TB hard drive storage. This new generation NVR is widely applied in the areas of public security, education, communication, transportation, military, finance/banking and various other installation applications.

- Linux Embedded System
- H.265/H.264/MPEG-4 Video Stream Input
- HDMI/VGA Output up to 4k
- PoE Supported
- 1TB Hard Drive Included
- Maximum Storage Capacity: 8 TB
- Remote Live View By Mobile App
- 5 Year Limited Warranty (Excluding Hard Drive)
- 3 Year Limited Warranty (Hard Drive in Recorder)

PART #: OE-4CHNVRNG

UPC: 840049300576

LENGTH: 10.1"

WIDTH: 9.25"

HEIGHT: 1.8"

WEIGHT: 2.1bs



**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.
FOR TECHNICAL SUPPORT: 1-833-574-9124**

wboxtech.com

Specifications

| | |
|---|---|
| Model | 0E-4CHNVRNG |
| VIDEO/AUDIO INPUT | |
| Video Input | 4ch |
| Incoming Bandwidth | 40Mbps ,(main stream 32Mbps ,sub stream 8Mbps) |
| Outgoing Bandwidth | Total 40Mbps |
| Audio Input | G711_A/G711_U |
| VIDEO/AUDIO OUTPUT | |
| Live View/Playback/ Recording Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/720P/D1, etc |
| Frame Rate | 8MP/6MP/5MP/4MP/3MP@15fps; 1080P@30fps; |
| Live View/Playback Resolution | Live View: 4ch 1080P/1ch 8MP,@30fps |
| | Playback: 4ch 1080P/1ch 8MP |
| HDMI/VGA Output | 1920x1080/60Hz,1280x720/60Hz,1024x768/60Hz (HDMI up to 3840x2160) |
| Audio Output | 1ch line out. |
| HARD DISK | |
| SATA HDD | 1 SATA interface for 1HDD |
| Mounting Mode | Embedded |
| Capacity | Up to 8TB for each disk |
| NETWORK | |
| Network Interface | 1 RJ45 10M/100M network interface |
| Protocol | RTP/RTCP,TCP/UDP,HTTP,DHCP,DNS,NTP |
| POE Interface | 4ch 100Mbps ,IEEE802.3af |
| POE Max Power | 40W |
| INTERFACE | |
| HDMI/VGA | 1ch HDMI, 1ch VGA |
| USB | USB 2.0 x2 |
| Audio I/O | 1 in, 1 out |
| Alarm I/O | 4 in, 1 out |
| Reset Button | N/A |
| GENERAL | |
| Power Supply | DC 48V |
| Power Consumption | Less than 5W(without HDD,USB,POE) |
| Operating Temperature | -10°C ~ 45°C (14°F ~ 113°F) |
| Operating Humidity | 0% - 90% RH |
| Chassis | Smart 1U |
| Product Dimensions | 255x235x47.5mm |
| Product Weight | 1.93kg |